

**Technical features:**

- Steel case and striker, painted aluminium grey
- Dead-locking latch
- 12 V ac CE
- Rated current 2,5A

Supplied as standard:

- Striker
- 3 keys item 1.01070.10.1
- Fixing screws
- Instruction sheet


Standards:

- This electric lock series is certified according to the European standard EN 14846:06:
 - Security degree 3 (500 Kg lateral thrust and 200 Kg front load)

Hand:

- 1 = R.H. inwards 
- 2 = L.H. inwards 
- 3 = R.H. outwards 
- 4 = L.H. outwards 

Type	Description	Cylinder	Throws	Backset	Unit weight 	Pieces 	ITEM				
							Type	Dim.	Hand	Fin.	Pers. Spec.



- Inside push-button




1 02500 00 0

50	1,435	1	1	11610 50 1
50	1,440	1	1	11610 50 2
60	1,435	1	1	11610 60 1
60	1,445	1	1	11610 60 2
70	1,440	1	1	11610 70 1
70	1,450	1	1	11610 70 2
80	1,440	1	1	11610 80 1
80	1,440	1	1	11610 80 2



1 02552 50 0

50	1,445	1	1	11611 50 1
50	1,434	1	1	11611 50 2
60	1,440	1	1	11611 60 1
60	1,440	1	1	11611 60 2
70	1,445	1	1	11611 70 1
70	1,440	1	1	11611 70 2
80	1,439	1	1	11611 80 1
80	1,444	1	1	11611 80 2



- Inside push-button and cylinder
- Hold-open device



1 02104 00 0

50	1,538	1	1	11630 50 1
50	1,523	1	1	11630 50 2
60	1,533	1	1	11630 60 1
60	1,529	1	1	11630 60 2
70	1,500	1	1	11630 70 1
70	1,527	1	1	11630 70 2
80	1,536	1	1	11630 80 1
80	1,531	1	1	11630 80 2



1 02552 50 0

50	1,538	1	1	11631 50 1
50	1,538	1	1	11631 50 2
60	1,538	1	1	11631 60 1
60	1,538	1	1	11631 60 2
70	1,538	1	1	11631 70 1
70	1,538	1	1	11631 70 2