



TOUCH FREE EXIT DEVICE

HELPS STOP THE SPREAD OF GERMS

EXIT BUTTONS

Market leading request to exit buttons, that are both hard wearing and cost effective. Suitable for use in applications where contactless options are a priority.



EBNT/TF-1



SPECIFICATION

- EBNT/TF-1
- Contacts: Double pole NONC contacts
 - Contact Load: 0.5A @ AC 120V / 1A @ DC24V
 - Dual voltage 12/24 VDC @ 45mA operating
 - +/- 10% voltage tolerance
 - Etched legend (various options available)
 - Security screws (allen key type)
 - Button rated IP65 ingress protection
 - Adjustable relay opening times (0.5 to 20 sec)
 - Adjustable proximity distance (3 to 12 cm)
 - -10° to +70° operating temperature
 - Designed to prevent interference with other infra red devices

FEATURES

- EBNT/TF-1
- 38mm Touch free sensor button
 - Illumination - Green to red (or red to green)
 - High impact plastic back box
 - Can be surface or flush fitting
 - Easy clean surface
 - Ideal for general / sensitive areas
 - Screw footprint for flush fitting onto standard back box
 - Distance between fixing holes 60mm
- Suitable Alternative Back Boxes
- EXTR02 (Aluminium Extrusion 40mm)
 - SSBB02 (Stainless Steel Back Box 42mm)
 - PBB05 (Green or Black Back Box 40mm)

OTHER PRODUCTS

1201SM-1



RD26-C



ML600



DU-NT/TF



DIMENSIONS

- EBNT/TF-1
- 85x85x32 (mm)
 - 238g (Boxed)
 - 202g (Unboxed)

CONTENTS

- EBNT/TF-1
- Touch free button on SS Plate
 - Back box
 - Wires & connector
 - Screw bag
 - Instructions



Manufactured by a BSIA Member