



9945N5L Allgood Secure 99 Series Vertical Euro Profile Solenoid Redlock 12v DC Fail Secure (Left hand lever controlled)

- Compatible with every Allgood lever handle
- Outside handle controlled, lever withdraws latch bolt when solenoid is activated
- Inside lever always free to escape
- Reversible 19.8mm 3-part low friction deadlocking latch-bolt
- Supplied with reversible strike plate and mortar guard
- 12v DC fail secure *[fail locked/closed]*
- 200mA solenoid current draw
- Monitoring – Latch bolt, Request to exit and door status
- Supplied with simple push fit connections, plus a 5-metre doorway cable loom
- Additional 15 mm of lock mortise depth required to accommodate lock and cable loom connectors
- Incorporated in a successful fire test and assessed to BS EN 1634-1 and BS 476 Pt 22 up to 90 minutes on timber doors and 240 minutes on metal doors
- CE Marked & Certifire approved CF 623
- Independently tested to BS EN 179

3	7	6	B	1	3	4	2	A	B
---	---	---	---	---	---	---	---	---	---

3	7	6	B	1	3	4	2	A	D
---	---	---	---	---	---	---	---	---	---

- Underwriters Laboratories UL 10C electronic locking
- Compliant with ANSI 115.1. Suits standard ANSI preparation for metal doors
- 10-year mechanical warranty, 1-year electrical warranty (solenoid and microswitches)

Available Finishes: SS · PS · BF

